



DEGREASING AND CLEANING

# BESMA DEGREASER+WASH

CLEANING AGENTS BASED ON ADVANCED ENVIRONMENTAL TECHNOLOGY

## CLEANING GUIDE

### Besma Degreaser+Wash

Water-based degreaser for dissolving and removal of grease, oil, soot, fuel oil, excess of newly applied undercarriage protection and residues of asphalt. Suitable for cleaning tools, worktops, construction machinery, cars, engine- and machine rooms, as well as removing large amounts of oil from workshop floors.

### Mix Besma Degreaser+Wash with water according to the task

Task	Per 10 liters of water	Percentages
Items with thin oil film	5 dL	5%
Items with thick oil film	10 dL	10%
Fresh undercarriage protection agent	5 dL	5%
Mixing in cleaning/degreasing tank	2,5 L	25%
Construction machinery	5 dL	5%
Floors with large amounts of oil	1 L	10%
Diesel engines	1 - 2,5 L	10 - 25%
Engine rooms	1 - 2,5 L	10 - 25%
Fresh tar/asphalt stains	1 L	10%
For quicker effect	Undiluted	100%

Suitable for use with foam equipment.  
Apply to surface and leave to soak for 5-10 min.  
If necessary, use a brush.  
Rinse surface with plenty of clean water.  
Do not leave solution to dry on the surface  
and avoid washing in direct sunlight.



**Besma Degreaser+Wash**  
Causes serious eye damage.

**Danger**

Always read and follow product label information



©Besma International Chem a/s 2025

Environmental thought

Environmental action

Environmental Choice